Rig #17 Specifications

Drilling Range:	18,000' With 4-½" Drill Pipe
Drawworks:	TFI 1,500 HP
Mast:	Superior 136' High, Telescoping 750,000 lbs GNC 660,000 lbs Static Hook Capacity
Substructure:	Superior 20' High (10' Pony Available) 500,000 lbs Setback Capacity
Mud Pumps:	(2) Weatherford F-1,600, 7"x 12", 1,600 HP
Rotary Table:	TFI 27-½"
Automatic Catwalk	Canrig Powercat Model 3000
Floorhand	Blohm + Voss Oil Tools GF 1100 Auto Floorhand Wrench & Spinner
Traveling Assembly:	TFI 350 Ton Block/Hook Combination
Top Drive:	Canrig Model 1035, 350 Ton 30,000 ft-lb torque @ 200 RPM
SCR /Power System:	(3) 1,400 BHP Diesel Engines with 1,357 kW Generators Ross Hill SCR Unit
Mud System:	400 Total Barrels NOV Brandt Shakers
BOPE:	13-5M Annular, 13-5M Double Gate 120 Gallon Accumulator 5,000 psi Choke Manifold
Water/Fuel Storage:	400 BBLS/7,700 Gallons
Auxiliary Equipment:	(2) Hydraulic Winches Wireline Unit (.092") (2) Air Compressors Upper & Lower Doghouses Toolpusher Trailer