Rig #7 Specifications

Drilling Range:	25,000' with 5" Drillpipe
Drawworks:	National 1320 UE 2,000 HP
Mast:	DSI 142' High 1,300,000 lbs Static Hook Capacity with 10 lines
Substructure:	DSI 30' High 1,300,000 lbs Capacity
Mud Pumps:	(3) Weatherford MP-1600, 7"x 12", 1,600 HP
Rotary Table:	Oilwell 27-½", 500 Ton
Automatic Catwalk:	Canrig Powercat Model 3000
Floorhand:	Blohm & Voss Oil Tools GF 1100 Auto Floorhand Wrench & Spinner
Traveling Assembly:	Oilwell B-650 7 Sheave, 650 Ton Block
Top Drive	Canrig Model 1250 AC-681 500 Ton 51,400 ft-lb torque @ 120 rpm
SCR/Power System:	(4) 1,482 BHP Diesel Engines with 1,100 kW Generator Ross Hill SCR Unit
Mud System:	(3) Pit System, 1,400 Total Barrels NOV Brandt Shakers
B.O.P.E.:	13-5M Spherical Annular, 13-10 Double Gate, 13-10M Single Gate 260 Gallon Accumulator 10,000 psi Choke Manifold
Water/Fuel Storage:	400 BBLS/21,000 Gallons
Auxiliary Equipment:	(2) Air Winches Wireline Unit (.092") (2) Air compressors Upper & Lower Doghouses Toolpusher Trailer