Rig #3 Specifications

Drilling Range:	**20,000' with 4-½" Drillpipe**
Drawworks:	**Skytop Brewster N-12, 2,000 HP**
Mast:	**Superior 142' (Convertible to 112') High** **1,200,000 lbs GNC** **1,000,000 lbs Static Hook Capacity**
Substructure:	**20' High (10' Pony Available)** **1,200,000 lbs Capacity** **Walking System**
Mud Pumps:	**(2) National 12P-160 Triplex, 7"x 12", 1,600 HP**
Rotary Table:	**Continental Emsco 27-½"**
Automatic Catwalk:	**Canrig Powercat Model 3000**
Floorhand	**Blohm + Voss Oil Tools GF 1100 Auto Floorhand Wrench & Spinner**
Traveling Assembly:	**Oilwell 6 Sheave, 480 Ton Block/Hook and Oilwell 425 Ton Swivel**
Top Drive:	**Canrig Model 1250 AC-681 500 Ton** **51,400 ft-lb torque @ 120 RPM**
SCR/Power System:	**(3) 1,476 BHP Diesel Engines with 1,400 kW Generators** **CARB Compliant** **Ross Hill 4 Bridge, 4 Input SCR** **Highline Connection**
Mud System:	**(2) Pit System, 1,000 Total Barrels** **(2) NOV Brandt Shakers**
BOPE:	**Hydril GK 11-5M Annular, Hydril 11-5M Double Gate** **Koomey 120 Gallon Accumulator** **5,000 psi Choke Manifold**
Water/Fuel Storage:	**400 BBLS/12,300 Gallons**
Auxiliary Equipment:	**(2) Air Winches** **Wireline Unit (.092")** **(2) Air compressors** **Upper & Lower Doghouses** **Toolpusher Trailer**